	KEPUKI DOCU	MENTATION	PAGE		
a. REPORT SECURITY CLASSIFICATION	16 RESTRICTIVE MARKINGS				
Unclassified					
			AVALABILITY OF i for Publi		_
	DULE		tion Unlim		e
AD 4400 000	BER(S)				······································
4D-A198 988	gen(3)	5 MONITORING	ORGANIZATION RE	PORT NUMBER	(5)
		1			
NAME OF PERFORMING ORGANIZATION Department of Chemistry	6b OFFICE SYMBOL (If applicable)	74 VAME OF M	ONITORING ORGAN	IZAT ON	<del> </del>
University of North Care		Office	of Naval	Research	
e ADDRESS City, State, and ZIP Code)	<del></del>		ly, State, and ZIP C		
		Depart	ment of th	e Navy	
Chapel Hill, North Caro	lina 27514	Arling	gton, VA 22	217	
a. NAME OF FUNDING SPONSORING	86 OFFICE SYMBOL	9 PROCUREMEN	T INSTRUMENT CE	NTECATION V	LMBER
ORGANIZATION	(If applicable)	N00014-	86-K-0608		
C ADDRESS (City, State, and ZIP Code)		10 10: 257 05	FUNDING NUMBE?		
E 1001ESS (City, State, 2nd 2in Code)		PROGRAM	PROJECT	,72<	MORK UNIT
		ELÉMENT NO	NO	٧٥	ACCESSION NO
	: 01 L 20 T		<u> </u>	NR 053-6	
* TTLE (include Security Classification) US				erizatio	n of
BiCaSrCuO and BiSnCa	Srcuo Supercon	auction Cer	omalcs		
¿ FERSCHAL AUTHOR(S) John H. MI.	ller, Jr., Wil	li am E. Ha	atfield, Br	ian R. R	ohrs, Mari
. Kirk, Joanna L. Perkin:		L. Trojan,	John D. Hu ORT (Year, Month	inn, Zu H	ua Zhang
17 LAGE UP TERUTAL TITLE CHARL	COVERED	114 DATE OF REPO	ORT (Year, Month	Jay) [15 PAG	E CO .NI
	*0	1988 Septe	ember 20	ļ.	11
Technical Report FROM_	*0	1988 Septe	ember 20		
Technical Report FROM_	*o	1988 Septe	ember 20		11
Technical Report FROM_ 6 SUPPLEMENTARY NOTATION Technical Report No. 32		1300 Depte	ember 20		
Technical Report FROM 6 SUPPLEMENTARY NOTATION	18 SUBJECT TERMS	Continue on reven	e if necessary and	d dentify by bi	ock number)
Technical Report FROM_ 6 SUPPLEMENTARY NOTATION Technical Report No. 32 7 COSATI CODES	'8 SUBJECT TERMS  magnetic su	Continue on reven	e if necessary and	didentify by bi	ock number) surements,
Technical Report FROM	magnetic su Rutherford	Continue on revense sceptibility backscatter energy di	e if necessary and ty, resista	dentify by bi	oxx number) surements,
Technical Report FROM	magnetic su Rutherford microscopy	Continue on reven sceptibilit backscatter energy dis	e if necessary and ty, resista ring, scanr spersive X-	dentify by bi ance meas ning elec- ray anal	ox number) surements, stron yses.
Technical Report FROM	magnetic su Rutherford microscopy of and dentify by block ity measuremen	Continue on revense sceptibility backscatter energy discumber)	w if necessary and ty, resistant sing, scann spersive X-	ince measing electray anal	ox number) surements, tron yses. Rutherfor
Technical Report FROM	magnetic su Rutherford microscopy, and dentify by block ity measuremen electron micro.	sceptibility backscatter energy distributer to the company of the	ty, resistating, scannespersive X-	ince measing electray anal	ox number) surements; tron yses. Rutherfor X-ray
Technical Report FROM	magnetic su Rutherford microscopy, y and dentify by block ity measuremen electron microsorder to dete	continue on revense sceptibility backscatter energy disnumber) ts, resistate scopy, and rmine the e	ty, resistating, scann spersive X- ance measurenergy diseffects of	denuty by but ance meas a ring electron anal ements, spersive composit	cx number) surements, etron yses. Rutherfor X-ray ion and
Technical Report FROM	magnetic su Rutherford microscopy, y and dentify by block ity measuremen electron microsorder to dete	continue on revense sceptibility backscatter energy disnumber) ts, resistate scopy, and rmine the e	ty, resistating, scann spersive X- ance measurenergy diseffects of	denuty by but ance meas a ring electron anal ements, spersive composit	cx number) surements, etron yses. Rutherfor X-ray ion and
Technical Report FROM	magnetic su Rutherford microscopy, y and dentify by block ity measuremen electron microsorder to dete	continue on revense sceptibility backscatter energy disnumber) ts, resistate scopy, and rmine the e	ty, resistating, scann spersive X- ance measurenergy diseffects of	denuty by but ance meas a ring electron anal ements, spersive composit	cx number) surements, etron yses. Rutherfor X-ray ion and
Technical Report FROM 6 SUPPLEMENTARY NOTATION  Technical Report No. 32  Technical Report From No. 32  Technical Report No. 32  Technical Report No. 32	magnetic su Rutherford microscopy, ny and density by block ity measuremen electron micro order to dete properties of	continue on revense sceptibility backscatter energy disnumber) ts, resistate scopy, and rmine the e	ty, resistating, scann spersive X- ance measurenergy diseffects of	denuty by but ance meas a ring electron anal ements, spersive composit	cx number) surements, etron yses. Rutherfor X-ray ion and
Technical Report FROM	magnetic su Rutherford microscopy, ny and density by block ity measuremen electron micro order to dete properties of	continue on revense sceptibility backscatter energy disnumber) ts, resistate scopy, and rmine the e	ty, resistating, scann spersive X- ance measurenergy diseffects of	denuty by but ance meas a ring electron anal ements, spersive composit	cx number) surements, etron yses. Rutherfor X-ray ion and
Technical Report FROM	magnetic su Rutherford microscopy, ny and density by block ity measuremen electron micro order to dete properties of	continue on revense sceptibility backscatter energy disnumber) ts, resistate scopy, and rmine the e	ty, resistating, scann spersive X- ance measurenergy diseffects of	denuty by but ance meas a ring electron anal ements, spersive composit	cx number) surements, etron yses. Rutherfor X-ray ion and
Technical Report FROM	magnetic su Rutherford microscopy, ny and density by block ity measuremen electron micro order to dete properties of	continue on revense sceptibility backscatter energy disnumber) ts, resistate scopy, and rmine the e	ty, resistating, scann spersive X- ance measurenergy diseffects of	ements, persive composito perconduc	Rutherfor X-ray ion and ting
Technical Report FROM SUPPLEMENTARY NOTATION  Technical Report No. 32  Technical Report No. 32	magnetic su Rutherford microscopy, ny and density by block ity measuremen electron micro order to dete properties of	continue on revense sceptibility backscatter energy disnumber) ts, resistate scopy, and rmine the e	ty, resistating, scann spersive X- ance measurenergy diseffects of	ements, persive composito perconduc	cx number) surements, tron yses. Rutherfor X-ray ion and

21 ABSTRACT SECURITY CLASSIFICATION 19 DISTRIBUTION AVAILABILITY OF ABSTRACT MUNCLASSIFIED/UNLIMITED ME SAME AS RET UNCLASSIFIED DTC SERS 226 FELEPHONE (Include Area Code) 22c OFFICE SYMBOL 120 NAME OF RESPONSIBLE NOIVIOUAL

DD FORM 1473, 84 MAR

33 APR edition may be used until exhausted All other editions are obsolete

SECURITY CLASSIFICATION OF THIS PAGE
UNCENE TED

- 12. and William J. Riley
- 18. superconducting ceramics

OFFICE OF NAVAL RESEARCH

Contract N000014-86-K-0608

R&T Code 413a001-000-01

TECHNICAL REPORT NO. 32

Synthesis and Characterization of BiCaSrCuO and BiSnCaSrCuO Superconducting Ceramics

by

John H. Miller, Jr., William E. Hatfield, Brian R. Rohrs, Martin L. Kirk, Joanne L. Perkinson, Kathleen L. Trojan, John D. Hunn, Zu Hua Zhang, and William J. Riley

The Departments of Chemistry and Physics, The University of North Carolina at Chapel Hill, North Carolina, 27599, U.S.A.

Prepared for publication in International Conference on the First Two Years of High Temperature Superconductivity, Tuscaloosa, AL, 11-13 April 1988

Reproduction in whole or in part is permitted for any purpose of the United States Government

\*This document has been approved for public release and sale, its distribution is unlimited.

\*This statement should also appear in Item 3 of Document Control Data - DD Form 1473. Copies of the form are available from the cognizant contract administrator.

SYNTHESIS AND CHARACTERIZATION OF BiCaSrCuO AND BiSnCaSrCuO SUPERCONDUCTING CERAMICS

JOHN H. MILLER JR.<sup>b</sup>, WILLIAM E. HATFIELD<sup>a</sup>, BRIAN R. ROHRS<sup>a</sup> MARTIN L. KIRK<sup>a</sup>, JOANNA L. PERKINSON<sup>a</sup>, KATHLEEN L.TROJAN<sup>a</sup>, JOHN D.HUNN<sup>b</sup>, ZU HUA ZHANG<sup>b</sup>, WILLIAM J. RILEY<sup>b</sup>

The Departments of Chemistry<sup>a</sup> and Physics<sup>b</sup>, The University of North Carolina at Chapel Hill, Chapel Hill, North Carolina 27599, U.S.A.

Abstract Magnetic susceptibility measurements, resistance measurements, Rutherford backscattering, scanning electron microscopy, and energy dispersive X-ray analyses were utilized in order to determine the effects of composition and firing conditions on the properties of the Bi-Ca-Sr-Cu-O superconducting ceramics.

## INTRODUCTION

New high - temperature superconducting materials with  $T_{\rm C}$ 's in the range of 120K have recently been realized in both the Tl-Ca-Ba-Cu-O<sup>1</sup> and Bi-Ca-Sr-Cu-O<sup>2</sup> systems. These systems consist of at least two superconducting phases characterized by their superconducting transition temperatures of ~80K and ~120K. The transition temperature, critical current density, anisotropic properties, and volume fraction of the superconducting



Accession For

NTIS GRAMI
DTIC TAB
Unannounced
Justification

By
Distribution/
Availability Codes

Availability Codes

Dist Special

material are inherently related to the microstructure of the ceramics. In this report, we have investigated the effects of starting composition, Sn doping, and annealing and sintering conditions on the magnetic and electrical properties, microstructure, surface stoichiometry, and multiphasic nature of the Bi-Ca-Sr-Cu-O system.

## EXPERIMENTAL

## Synthesis

Samples of the Bi-Ca-Sr-Cu-O ceramics were synthesized via intimate mixing of Bi<sub>2</sub>O<sub>3</sub>, CuO, CaCO<sub>3</sub>, and SrCO<sub>3</sub> by thoroughly grinding the starting materials. This was followed by pressing into a pellet and sintering at 880°C (sample 1), doping with SNO and SNO<sub>2</sub>, pressing into a pellet, sintering at 880°C, and annealing at 950°C for 15 minutes (sample 2), pressing into a pellet, and sintering at 820°C (samples 3 and 4). All materials were sintered and annealed in air in a muffle furnace. The ratios of the starting materials are given in Table 1.

TABLE I Molar ratios of starting materials

Sample	Bi-Sn-Ca-Sr-Cu molar ratios		
1	2-0-1-2-2		
2	2-1-1-2-2		
3	1-0-1-1-2		
4	2-0-1-2-2		

## SUPERCONDUCTING CERAMICS

#### Magnetic Measurements

Quantitative magnetic measurements were made using a vibrating sample magnetometer equipped with a continuous flow cryostat. The samples were cooled in zero field (ZFC) to 4.2K, and the diamagnetic shielding data was collected past the transition temperature in a field of 50 Oe. The sample was then field cooled (FC) through the transition temperature in order to monitor the Meissner effect. The density of the samples was measured and volume susceptibilities were determined. All data was corrected for demagnetization effects.

## Resistance Measurements

Resistance measurements were made from 20~300K utilizing an in-line four-probe technique. Compensation for the Seebeck effect was made.

# Surface Analysis

The surface, microstructure, and stoichiometry of the superconducting ceramics were determined by Rutherford backscattering (RBS) and scanning electron microscopy - energy dispersive X-ray analysis (SEM-EDX). A standardless semi-quantitative analysis program was used to determine the elemental analysis of the bulk material as well as that of the individual grains.

# RESULTS AND DISCUSSION

Transition Temperature and Superconducting Volume Fractions
The magnetic data for the four samples studied show

relatively broad transitions, indicative of the multiphase nature of the samples. Sample 1 displayed the greatest volume fraction of superconducting material, with 8.4% bulk diamagnetism in the Meissner signal and 13.1% for the maximum diamagnetic shielding. The  $T_{\rm c}$  for sample 1 was monitored by both resistance and magnetic measurements. The onset temperature of the decrease in resistance was 87K, with zero resistance being realized at 37K. magnetic data determined the  $T_{\text{C}}$  to be 77.6K for the ZFC run and 79.5K for the FC data set. The anomolously low temperature necessary for zero resistance is most probably due to contact problems or the percolative nature of the superconductivity. The results of the critical temperatures and diamagnetic fractions are summarized in Table II.

# Surface Analysis and Microstructure

RBS of samples 1 and 2 yielded valuable information concerning the constitution of the sample surface. The surface stoichiometries (Bi-Sn-Sr-Ca-Cu) were determined to be (1:0.0:0.7:1.0:1.5) and (1:0.53:1.27:0.93:1.33) respectively. This data indicates that the surface is rich in Ca and Cu, with the latter probably being present in the form of oxides.

An EDX elemental analysis of sample 1 yielded a stoichiometry of  $Bi_{1.43}Sr_{1.62}Ca_{0.61}Cu_{2.00}$  and the SEM showed the material to be very porous with little or no melting. Analysis of single grains confirmed the multiphasic nature of the composite, however some grain of different morphology displayed very similar stoichiometries.

# SUPERCONDUCTING CERAMICS

TABLE II Transition temperatures and percent bulk diamagnetism

Sample	T <sub>C</sub> (ZFC)	T <sub>C</sub> (FC)	T <sub>C</sub> (onset)	T <sub>c</sub> (zero)	%(2FC)	₹(FC)
1	77.6	79.5	87	37	13.1	9.4
2	72.3	76.9	88	61	8.2	1.6
3	69.5	72.7			5.6	4.1
4	73.5	73.5			1.0	0.7

The overall stoichiometry of sample 2 was  $Bi_{0.61}Sn_{0.55}Sr_{1.28}Ca_{0.90}Cu_{2.00}$ . Analysis of single grains showed large areas of Sr depletion. As in the case of sample 1, no melting was observed and the individual grains were of widely differing morphology and composition.

Sample 3 was very homogeneous and individual grains had stoichiometries similar to that of the bulk  $(Bi_{1.50}Sr_{0.91}Ca_{1.07}Cu_{2.00})$ . However, we did find areas heavily depleted in Bi, Sr, and Ca. In contrast to the previous ceramics, SEM showed some melting had occurred resulting in partial fusion of the grains in an annealed pellet. Analysis of some unannealed sintered powder yielded some lamellar grains of composition  $Bi_{1.7}Sr_{1.4}Ca_{0.9}Cu_{2.0}$ .

EDX of the final sample indicated severe Ca depletion. The sample was polycrystalline and very homogeneous (1 $\mu$  dia.). As in the case of the first two ceramics, the pressed pellet was very porous.

## CONCLUSIONS

1

The samples studied were generally multiphase in nature and very porous. The transition temperatures were found to be dependent on the molar ratios of the starting materials and firing conditions, but generally, the Tc's correspond to the 80K phase. More intimate mixing of the precursors must be obtained in order to increase the homogeneity of the fired material and increase the yield of the superconducting fraction. It may be that the best reaction conditions for the highest yields occur in a very narrow temperature range, requiring precise control of the firing temperature.

#### REFERENCES

- 1. a) Z. Z. Sheng and A. M. Hermann, <u>Nature</u>, <u>332</u>, 55 (1988).
  - b) 2. 2. Sheng and A. M. Hermann, <u>Nature</u>, <u>332</u>, 138 (1988).
- 2. a) H. Takahi, H. Eisaki, S. Uchida, A. Maeda, S. Tajima, K. Uchinodura and S. Tanaka, Nature, 323, 256 (1988).
  - b) R. M. Hazen, C. T. Prewitt, R. J. Angel, N. L. Ross, L. W. Finger, C. G. Hadidiacos, D. R. Veblen, P. J. Heaney, P. H. Hor, R. L. Meng, Y. Y. Sun, Y. Q. Wang, Y. Y. Xue, Z. J. Huang, L. Gao, J. Bechtold, and C. W. Chu, Phys. Rev. Lett., 60, 1174 (1988).

## **ACKNOWLEDGEMENTS**

This work was supported in part by the Office of Naval Reasearch. J.H.M. acknowledges the receipt of an A.P. Sloan Research Fellowship, and R.J. Reynolds Faculty Development Award, and a grant from the U.N.C. Research Council.

# 01/1113/87/2

# TECHNICAL REPORT DISTRIBUTION LIST, GEN

	No. Copies		No. Copies
Office of Naval Research Attn: Code 1113 800 N. Quincy Street Arlington, Virginia 22217-5000	2	Dr. David Young Code 334 NORDA NSTL, Mississippi 39529	1
Dr. Bernard Douda Naval Weapons Support Center Code 50C Crane, Indiana 47522-5050	1	Naval Weapons Center Attn: Dr. Ron Atkins Chemistry Division China Lake, California 93555	I
Naval Civil Engineering Laboratory Attn: Dr. R. W. Drisko, Code LS2 Port Hueneme, California 93401	1	Scientific Advisor Commandant of the Marine Corps Code RD-1 Washington, D.C. 20380	1
Defense Technical Information Center Building 5, Cameron Station Alexandria, Virginia 22314	12 high quality	U.S. Army Research Office Attn: CRD-AA-IP P.O. Box 12211 Research Triangle Park, NC 27709	1
DTNSRDC Attn: Dr. H. Singerman Applied Chemistry Division Annapolis, Maryland 21401	1	Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, Pennsylvania 1911	2
Or. William Tolles Superintendent Chemistry Division, Code 6100 Naval Research Laboratory Washington, D.C. 20375-5000	1	Naval Ocean Systems Center Attn: Dr. S. Yamamoto Marine Sciences Division San Diego, California 91232	1

# ABSTRACTS DISTRIBUTION LIST 053

Dr. M. F. Hawthorne Department of Chemistry University of California Los Angeles, California 90024

Professor O. T. Beachley Department of Chemistry State University of New York Buffalo, New York 14214

Dr. W. Hatfield
Department of Chemistry
University of North Carolina
Chapel Hill, North Carolina 27514

Professor R. Wells Department of Chemistry Duke University Durham, North Carolina 27706

Professor K. Neidenzu Department of Chemistry University of Kentucky Lexington, Kentucky 40506

Dr. Herbert C. Brown Department of Chemistry Purdue University West Lafayette, IN 47907 Dr. J. Zuckerman Department of Chemistry University of Oklahoma Norman, Oklahoma 73019

Professor R. Neilson Department of Chemistry Texas Christian University Fort Worth, Texas 76129

Professor M. Newcomb Department of Chemistry Texas A&M University College Station, Texas 77843

Professor L. Miller Department of Chemistry University of Minnesota Minneapolis, Minnesota 55455

Professor K. O. Christe Rockwell International Canoga Park, California 91304

Dr. Margaret C. Etter Department of Chemistry University of Minnesota Minneapolis, MN 55455

